

Automatic controllers



Performance features

- » For automatic regulating of ventilation controllers
- » Temperature or time-controlled automatic

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

RTR 231

30.902.20

Room temperature control

- » For automatically controlling ventilation flaps in conjunction with 230 V AC ventilation drives
- » Surface-mounted design
- » For 24 V DC and 230 V AC systems



Input voltage	230 V AC
Type of protection	IP 30
Temperature range	5 °C ... 30 °C
Housing	Plastic
Colour	White
W x H x D	78 x 83 x 28 mm
Weight	0.10 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

ITR 79

64.800.03

Temperature regulator with external sensor

- » With isolated toggle
- » Larger control panel housings are required for installation in compact or modular GVL-K, GVL-M or RZN-K, RZN-M control panels
- » Can be used on site using surface-mounted housing GEH-TR02
- » Adjustable operating range from -10 °C ... +40 °C, operating differential 0.5 ... 5 K
- » Optional with wall-mounted, external or suspended sensor



Input voltage	230 V AC
Housing	Plastic
Colour	Grey
W x H x D	35 x 86 x 61 mm
Weight	0.21 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

TR 608

64.801.28

1-channel timer

- » Requirements-based programming option, e.g. end of workday CLOSED (Mon.-Thu. 6:00 p.m. CLOSED, Fri. 3:00 p.m. CLOSED)
- » Larger control panel housings are required for installation in compact or modular GVL-K, GVL-M or RZN-K, RZN-M control panels
- » Can be used on site using surface-mounted housing GEH-TR02



Input voltage	230 V AC
Housing	Plastic
Colour	Grey
W x H x D	17.9 x 65.5 x 85.5 mm
Weight	0.16 kg

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

TR 612

64.800.28

2-channel timer

- » Requirements-based programming option, e.g. end of workday CLOSED (Mon.-Thu. 6:00 p.m. CLOSED, Fri. 3:00 p.m. CLOSED)
- » Larger control panel housings are required for installation in compact or modular GVL-K, GVL-M or RZN-K, RZN-M control panels
- » Can be used on site using surface-mounted housing GEH-TR02

Input voltage	230 V AC
Housing	Plastic
Colour	Grey
W x H x D	35 x 65.5 x 86 mm
Weight	0.16 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

GEH-TR02

63.600.88

Surface-mounted housing for ITR and TR

- » For surface-mounted installation of supporting rail modules
- » With viewing window

Housing	Plastic
Colour	Light grey
W x H x D	150 x 80 x 98 mm
Weight	0.20 kg



